

Certificate of Conformity

By the product certificate number:

i

No. 2622/0301-C-CER

Issued to:

License holder:

AISWEI Technology (Shanghai) Co., Ltd.

Room 905B, 757 Mengzi Road, Huangpu District,

200023 Shanghai, P.R. China

Trademark:

📤 Solplanet

Manufacturer:

AISWEI New Energy Technology (YangZhong) Co., Ltd. No. 588 Gangxing Road, Yangzhong, Zhenjiang, China

It is certified that the product:

Type of generating unit:

Grid-connected PV Inverter

Models:

ASW25K-LT-G3 / ASW27K-LT-G3 / ASW30K-LT-G3 / ASW33K-LT-G3 / ASW36K-LT-G3 / ASW40K-LT-G3

Technical Data:

Nominal power [W]

See page 2

Nominal voltage [V]

230 / 400

Nominal frequency [Hz]

50

Firmware version

Master Firmware version: V610-03041-05 Slave Firmware version: V610-60009-00 Safety Firmware version: V610-11007-02

Number of phases

Three Phases

Isolation Transformer

No

Is in compliance with the standard:

IEC 62116: 2014

Test procedure of islanding prevention measures for utility-interconnected photovoltaic inverters.

This certificate is based upon the test results of the Test Report GZES220400574703

The above-mentioned generating unit is certified according to the SGS internal procedure PE.T-ECPE-18 based on the requirements of the UNE-EN ISO / IEC 17065.

First issued on 30th June 2022 This certificate is valid until 30th June 2027

Madrid, 30th June 2022

Daniel Arranz Muñiz Certification Manager





SGS Tecnos, S.A. C/ Trespaderne, 29 - 28042 Madrid
This certificate is issued by SGS under its General Conditions
for Product Certification at www.sgs.com/terms and conditions.
The status and validity of the certificate can be checked scanning the
QR code above included or through the following web link database:
https://www.sgs.com/en/certified-clients-and-products/electrical-products
This document cannot be reproduced partially







Full list of product references and nominal characteristics:

Product Model	ASW25K-LT-G3	ASW27K-LT-G3	ASW30K-LT-G3
Input (DC)			
Max.DC Voltage (V)	1100		
MPPT Voltage Range (V)	180 ~ 1000		
Full load DC voltage range (V)	450 ~ 850		
Max. input current (A)	32/32/32		
	Output (A0	C)	
Rated active power (W)	25000	27000	30000
Max. apparent AC power (VA)	27500	29700	33000
Max. Output Current (A)	39.9	43.0	47.8
Nominal Grid Voltage (V)	230 / 400 (3 /N/PE)		
Nominal Frequency (Hz)	50		

Product Model	ASW33K-LT-G3	ASW36K-LT-G3	ASW40K-LT-G3
Input (DC)			
Max.DC Voltage (V)	1100		
MPPT Voltage Range (V)	180 ~ 1000		
Full load DC voltage range (V)	450 ~ 850		
Max. input current (A)	32/32/40		
	Output (A0	C)	
Rated active power (W)	33000	36000	40000
Max. apparent AC power (VA)	36300	39600	44000
Max. Output Current (A)	52.6	57.4	63.8
Nominal Grid Voltage (V)	230 / 400 (3 /N/PE)		
Nominal Frequency (Hz)	50		



